



## Telephone Products

Model	Description	
b-line UNIT 	<b>b-line - Digital ISDN / POTS Hybrid and Phone System</b> System includes: half 19" 1U b-line Unit and Accessories incl. wall power supply, 19" rack mounting kit, ISDN and POTS cable, (#YT6000) Yellowtec-CD with Talkmaster® software (#YT6001)	€
b-line A UNIT 	<b>b-line - Digital DUAL POTS Hybrid and Phone System</b> System includes: half 19" 1U b-line A Unit with two analogue line interfaces (POTS) instead of an ISDN/POTS combination and Accessories incl. wall power supply, 19" rack mounting kit, POTS cables, (#YT6020) Yellowtec-CD with Talkmaster® A software (#YT6021)	€
<h3>b-line Accessories</h3>		
b-line HAND	<b>b-line Handset</b> To be connected to b-line's PreTalk (Handset/phone) interface to screen callers before switching them on air in ISDN mode (#YT6002)	€
b-line HEAD	<b>b-line Headset</b> To be connected to b-line's PreTalk (Handset/phone) interface to screen callers before switching them on air in ISDN mode (#YT6003)	€
b-line PHONE	<b>b-line Phone</b> POTS telephone to be connected to b-line's PreTalk (Handset/phone) interface to screen callers before switching them on air in analogue a/b mode (#YT6004)	€
b-line KEY 	<b>b-line Keypad</b> For external control with the genuine feeling of real buttons. To be connected to b-line's RS-232 interface. It offers access to all main functions like PreTalk (for off-air call screening), Hold, On-Air and Drop. It includes a built-in function display, 10 number speed dial memory, phone book access, 0-9 numeric display. A spliss cable for the RS-232 connection and for insertion of 5V DC from a wall power supply is included too (#YT6005)	€
b-line DUAL	<b>b-line Dual 19" Rack Mounting Kit</b> For the installation of 2 b-line units in a 19" 1U space (#YT6006)	€
b-line DTMF	<b>b-line DTMF Generator/Analyser</b> To initiate calls, to send DTMF tones over already set-up connections, or to compute/evaluate DTMF tones (e.g. in competitions). A software key will be supplied to enable the functionality (#YT6007)	€
b-line RACC	<b>b-line Remote Access Software</b> Requires an ISDN PC card and one USB interface for the software dongle (#YT6008)	€



## SmartCard Products

Model	Description	
IMX	 <p><b>Intellimix - 3 Fader Digital Desktop Mixer / Router</b> System includes: 19" 1U Base Unit (#YT2001), Control Unit (#YT2002), Accessories (#YT2003) incl. SmartCard, Configuration Software, RS-232 and remote cable, microphone insert plugs</p>	€
VIP/d	 <p><b>VIP/digital – Digital Voice Processor</b> System includes: 19" 1U Base Unit (#YT1000), Accessories (#YT1001) incl. SmartCard, Configuration and Remote Software</p>	€

## Accessories SmartCard Products

SC	<p><b>SmartCard</b> Personal data card for Intellimix and VIP/digital (#YT3000)</p>	€
Loom1	<p><b>Intellimix Analogue I/O Loom</b> for Intellimix Line Input 7 &amp; 8 / Mix Output, 15pin Sub-D to 2 x XLR-Male / 2 x XLR-Female (#YT2100)</p>	€
Loom2	<p><b>Intellimix Digital I/O Loom</b> for Intellimix Mic-Insert 1 &amp; 2 or Line Input 13-16 / Mix Output, 9pin Sub-D to 1 x XLR-Male / 1 x XLR-Female (#YT2101)</p>	€
Loom3	<p><b>Intellimix Analogue-In Loom</b> for Intellimix Line Input 9 &amp; 10, 9pin Sub-D to 2 x XLR-Female (#YT2102)</p>	€
Loom4	<p><b>Intellimix Mix-Minus Loom</b> for Intellimix Mix-Minus Out, digital and analogue, 9pin Sub-D to 3 x XLR-Male (#YT2103)</p>	€
Loom5	<p><b>Intellimix Monitor-Out Loom</b> for Intellimix Monitor-Out, balanced analogue, 25pin Sub-D to 2 x XLR-Male (#YT2104)</p>	€
Loom6	<p><b>Intellimix Monitor/External Loom</b> for Intellimix Monitor-Out and External-In, analogue and digital, 25pin Sub-D to 5 x XLR-Male / 3 x XLR-Female (#YT2107)</p>	€
ConSet	<p><b>Intellimix Connector-Set</b> All necessary Sub-D connectors for complete Intellimix installation, 2 x Sub-D 25pin, 2 x Sub-D 15pin, 10 x Sub-D 9pin (#YT2105)</p>	€

## Interface Products

Model	Description	
PUC S/PDIF 	<b>PUC S/PDIF - Professional USB Converter</b> PUC'n'Play USB Audio Interface, Windows 98-2000-XP and MAC OS9-OSX compatible, installation with plug-in (i.e. no additional drivers are needed), balanced analogue (+4/6dBu) <u>and parallel S/PDIF</u> I/O (#YT4000)	€
PUC AES/EBU 	<b>PUC AES/EBU - Professional USB Converter</b> PUC'n'Play USB Audio Interface, Windows 98-2000-XP and MAC OS9-OSX compatible, installation with plug-in (i.e. no additional drivers are needed), balanced analogue (+4/6dB) <u>and parallel AES/EBU</u> I/O (#YT4001)	€

## Accessories USB Products

Loom-S	<b>PUC S/PDIF Loom</b> for balanced analogue I/O (4 x XLR), digital S/PDIF I/O (2 x RCA) and 9pin Sub-D for GPIs "Level, ZLM, digital Bypass" (#YT2108)	€
Loom-A	<b>PUC AES/EBU Loom</b> for balanced analogue I/O (4 x XLR), for digital AES/EBU I/O (2 x XLR) and 9pin Sub-D for GPIs "Level, ZLM, digital Bypass" (#YT2110)	€
Loom-VX	<b>PUC VX222 Loom</b> for interconnection of PUC to existing Digigram VX222 cable sets (#YT2109)	€

## m!ka Microphone Arms

Model	Description	
MIKARM	<p><b>m!ka Microphone Arm</b> Elegant single tube construction with elaborate internal linkage and coil spring construction supporting mics up to 2 kg. Internally wired with open cable tails for user fitting of connectors. Available in two finishes without microphone: coated with non-glare <u>dark grey</u> (#YT3200) natural <u>aluminium</u> (#YT3201)</p>	€ €
MIKARM ON AIR	<p><b>m!ka Microphone Arm "On Air"</b> Same as above, yet with On Air Signalling coated with non-glare dark grey (#YT3204) natural aluminium (#YT3205)</p>	€ €
BUSHING**	<p><b>m!ka Bushing</b> Stainless steel flush surface mounting bracket, suitable for material up to 52 mm thickness, 20mm thread diameter / 52mm head diameter (#YT3211)</p>	€
CLAMP	<p><b>m!ka Table Clamp</b> Clamp type bracket permits mounting mic arms on the edges of worktops, without the need to drill holes and without the need for additional tools, supports desk tops from 20 to 72mm, dark grey (#YT3210)</p>	€
MIC-to-POLE	<p><b>m!ka Mic Arm to MSS Pole Adapter</b> Bracket with height slider. Allows for attachment of multiple microphone arms to one singular MSS Pole. Body similar to Table Clamp (#YT3213)</p>	€

## m!ka Monitor Support System (MSS)

MONARM	<p><b>m!ka Monitor Arm</b> Reinforced two-part articulated arm with VESA 75/100 standard attachment, robust ball-and-socket joint for optimum viewing and quick-release catch for height adjustments. Supports TFT monitors up to 10 kg (#YT-3230)</p>	€
FLEXM	<p><b>m!ka Fleximount</b> Mount with VESA 75/100 standard attachment, robust ball-and-socket joint for optimum viewing and quick-release catch for height adjustments. Supports TFT and TV flat panel monitors up to 12kg (#YT-3231)</p>	€
POLE	<p><b>m!ka MSS Pole</b> Its four side profiles permit mounting of multiple Monitor Arms or Fleximounts. Plus: one Mic Arm can be plugged into the top! Standard lengths are: MSS Pole 17" / 445 mm (#YT-3240) MSS Pole 33" / 845 mm (#YT-3241)</p>	€ €
PDM-KIT	<p><b>m!ka Pole Desktop Mounting Kit</b> Professional attachment for the MSS Pole through a 10mm hole in the tabletop. Includes: M10x70 screw, washers, cable clamps (#YT-3245)</p>	€